

## PVC joint profile strips

DUROPLAST joint profile is designed to fill shrinkage and work gaps of industrial floors. It is a flexible profile made from PVC, which can be quickly and easily inserted into the joints. Ideal solution to provide an immediate plug for cut joints, which protects the joints from dirt and prevents edges to break off.

### PRODUCT CHOICE

DUROPLAST is available in two different sizes. You can choose the adequate size based on the thickness of the disk of cutting machine used:

Duroplast type	Thickness of disk	Thickness of profile
55 B	2,8 mm	3,8 mm
55 G	4,2 mm	6,0 mm

### PACKAGING

Delivered in 250 m rolls.

### TECHNICAL FEATURES

- Fast and clean installation
- can be inserted immediately after cutting
- Protects profile edges from cracking
- It does not age, rotten and quality is good for an indefinite time
- grey coloured
- can tolerate 2-3 mm of shrinkage of concrete

Occasionally, when the floor reaches its final drying period and shrinks to its final level, Duroplast might need to be changed for thicker version or to be switched for regular joint profile seal.

### INSTALLATION METHOD

Insertion of DUROPLAST can be made by using a special machine or by the help of a hammer. Ideal product, since it can be installed immediately after floor installation is finished.

### BEST BEFORE DATE

Indefinite and does not require special storage.

