

Water-based concrete curing liquid

DUROCURING is a ready to use impregnating, surface-treatment liquid that provides efficient curing and protection against drying for new floors constructed from plain concrete or with dry shake surface hardeners.

AREAS OF USE

- Industrial floors
- Monolithic concretes
- Indoor and outdoor concrete surfaces
- Cement based repair materials

FEATURES

- Easy to apply
- Eliminates dusting on concrete floor surfaces
- Ensures homogeneous, appropriate drying
- Limits the effects of cracking
- Can be applied to smooth or rough surfaces
- DUROCURING treated concrete floors are suitable for concrete paint, resin or ceramic coating
- Does not include silicone or any material, which could diminishes the attachment of new layer application
- Milk-white liquid

APPLICATION

DUROCURING should be spray applied to the surface of concrete immediately after the finishing operations.

USE OF MATERIAL

The quantity of DUROCURING used is highly dependent from weather conditions and the porosity of the concrete surface. In general, 80-100 gr. of curing liquid needs to be applied on a 1 m² surface. The suggested quantity should not be exceeded, because the excess material cannot blend into the surface and will create a yellowish white, wax-like coat on top of the surface. Though, this layer can be cleaned by mechanical cleaning.

PACKAGING

DUROCURING is supplied in 20 l jerry can and 120 liter drums.

STORAGE

Store in cool, but frost-free conditions.
Shelf life: 12 months.

SAFETY PRECAUTIONS

Water based product. Protect against freezing. Frozen product cannot be installed. Non-hazardous product.

